

IKO enertherm ALU NF

Product description:

IKO enertherm ALU is a 100 % CFC, HCFC or HFC-free insulation board with a rigid polyisocyanurate foam core, clad on both sides with a multi-layer gastight aluminium complex.

Application:

Sarking: pitched roof insulation (type nF with neutral felt).



Edge finish:



Tongue and groove (TG)

Thermal performance:

Thermal conduction coefficient: (EN 13165) λ_D : **0,022 W/(m.K)**

Fire properties

- Fire class according to EN 13501-1: **Class NPD**
- Fire class 'end use' according to 13501-1: **B-s2,d0 (steeldeck)**

Technical approvals:

Europe: CE - EN 13165: T2-DS(70,90)3-DS(-20,-)1-DLT(2)5-TR80 (≤ 140 mm) TR40 (< 140 mm)-CS(10Y)175-WL(T)1

Belgium: ATG 2726 - ATG 2727 - ATG H867

France: Certificat Acermi N° 06/103/434 DTA 5/13-2350

Netherlands: Komo Attest met Productiecertificaat CTG 485 Komo CTG 544

Germany: Bauaufsichtliche Zulassung Z 23.15-1611

USA: FM Factory Mutual

Availability:

Thickness (mm)		100	120	132	160
Rd (m ² .K/W)		4,50	5,45	6,00	7,25
2 400 x 1 200	m2/pac	5,76	5,76	5,76	5,76
	m2/pal	69,12	57,60	51,84	46,08