

IKO enertherm WOOD

Product description:


IKO enertherm WOOD is an insulation board that is 100% free from CFC, HCFC and HFC, with a rigid polyisocyanurate foam core, clad on both sides with a multilayer aluminium complex. It has a 9 mm OSB board on one side.

Application:

Comfort easy: loft floor insulation.



Edge finish:

 Rebate (SP)

Thermal performance:

Thermal conduction coefficient: (EN 13165) λ_D : **0,022 W/(m.K)**.

Technical details:

Bulk density of insulation board: $\pm 32 \text{ kg/m}^3$
 Weight of OSB: $\pm 5.4 \text{ kg/m}^2$
 Compressive strength at 10% deformation: $\geq 175 \text{ kPa (17.5 ton/m}^2)$
 Closed cells: **more than 95%**
 Water vapour diffusion resistance: PIR foam: $\mu = 60$, ALU facing: $\mu > 100,000$
 Formaldehyde class according to EN 120: **E1**
 OSB class according to EN 300: **OSB/3**

Fire properties

Fire class according to EN 13501-1: Class E
 Fire and smoke class: OSB according to EN 13986 DFL-s1

Availability:

Thickness (mm) - Insulation	50
Thickness (mm) - OSB board	9
1200 x 600 SP	2,29