

IKO enertherm ALU F4

Product description:


IKO enertherm ALU is a 100 % CFC, HCFC or HFC-free insulation board with a rigid polyisocyanurate foam core, clad on both sides with a multi-layer gastight aluminium complex. This high-quality reflecting ALU cladding consists of no fewer than seven layers, combined into a single complex. It is tested under extreme conditions in respect of water absorption, mechanical properties, corrosion resistance and emissivity.

Application:

Rooftop: flat roof insulation for timber, concrete and steel deck.



Edge finish:



Thermal performance:

Thermal performance: Thermal conduction coefficient: (EN 13165) λ_D : 0,022 W/(m.K)

Technical details:

- Bulk density: $\pm 32 \text{ kg/m}^3$
- Compressive strength at 10% deformation: 175 kPa (17,5 ton/m²)
- Behaviour under uniformly distributed loading: Class C ($\leq 5\%$ deformation at 70 °C and 40 kPa loading)
- Closed cells: more than 95%
- Water vapour diffusion: PIR foam: $\mu = 60$ - ALU facing: $\mu > 100,000$

Fire properties

Fire class according to EN 13501-1: Class E
 Fire class 'end use' according to 13501-1: B-s2,d0 (steeldeck)

Technical approvals:

Europe: CE - EN 13165: T2-DS(70,90)3-DS(-20,-)1-DLT(2)5-TR80 (≤ 140 mm) TR40 (> 140 mm)-CS(10Y)175-WL(T)1
 Belgium: ATG 2726 - ATG H867
 France: Acermi N° 18/103/1398
 Netherlands: Komo kwaliteitsverklaring CTG 485
 Germany: Q-Zeichen PU-244.0-04
 UK: BBA 15/5283
 USA: FM Factory Mutual

Availability:

Thickness (mm) Rd (m ² .K/W)		50	60	70	80	85	90	100	110	120	130	140	160	180	200
		2,25	2,70	3,15	3,60	3,85	4,05	4,50	5,00	5,45	5,90	6,35	7,25	8,15	9,05
1 200 x 600	m2/pack	-	5,76	-	4,32	-	-	3,60	-	2,88	-	2,16	-	-	-
	m2/pal	-	57,60	-	43,20	-	-	36,00	-	28,80	-	25,92	-	-	-
2 400 x 1 200	m2/pack	28,80	23,04	20,16	17,28	14,40	11,52	14,40	11,52	11,52	11,52	8,64	5,76	5,76	5,76
	m2/pal	144,00	115,20	100,80	86,40	86,40	80,64	72,00	57,60	57,60	57,60	57,60	46,08	40,32	34,57